



6MP Full Color Turret IP Camera

Model: IP-2366F28





Features:

- ❖ 1/3" CMOS sensor
- ❖ 6MP realtime resolution 3072x2048
- ❖ Low illumination 0.01Lux
- ❖ Day/Night, AWB/MWB, BLC, HLC, 2D/3D-DNR, Shutter
- ❖ D-WDR, Mirror, rotate, Defogging
- ❖ Multiply Style OSD Overlay, Motion Detection, Privacy Mask
- ❖ RTSP and ONVIF 17.06 compatible with many third-party NVR
- ❖ H.264/H.265 dual-stream media server
- ❖ Support user authentication, video data encryption
- ❖ Support Alarm Snapshot to Email and FTP
- ❖ Multiply WEB browser IE, Firefox 32bit ESR, PC Client
- ❖ RJ45 100mbps network port, IEEE802.3af PoE
- ❖ Lightning protection 4000V
- ❖ Strong water-proof housing, IP66
- ❖ 2 pcs white LED warm light, distance 20-30 meters
- ❖ HD 2.8mm F1.2 lens
- ❖ [Vehicle & human body detection](#)
- ❖ [Built-in Microphone](#)

Technical Specifications:

Model	IP-2366F28
Camera	
Image Sensor	1/3" CMOS
Effective Pixels	6 megapixels
Electronic Shutter	AUTO, 10-10000/min
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Manual
BLC /HLC	Support
DNR	2D/3D DNR
Other	AGC, Motion Detection, Privacy Mask, Flip, OSD Overlay
Encode	
Video Standard	H.264/H.265
Video Resolution	Main Stream: 25fps@6MP(3072x2048)/25fps@5MP(2592x1944)/4MP(2592x1520)/3MP , 30fps@1080P/720P Sub stream: 25fps@D1/VGA/360P/CIF, etc.
Video Bitrates	512Kbps - 12Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a
Built-in Mic	Yes
OSD Overlay	Title and Time overlay
LEDs	
LEDs	2 pcs white LED warm light
Distance	20-30M
Lens	
Focal length	2.8mm F1.2 lens
Optional Function	
PoE, Audio, Vehicle & human body detection	
Network Services	
Protocol	HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.
P2P	Yes
Web	IE, Firefox (32bit esr), etc.
Media	CMS, Android, IOS
ONVIF	17.06 compatible
General	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	Default: PoE (12V DC $\pm$ 10% optional)
Power Consumption	< 8 W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH